

Rainfall Blocker Waterproofing

IMPERMEABILIZANTE PAREDE

PRODUCT

It is a white acrylic sealer, which is intended to eliminate water infiltrations caused by rainfall can be applied to vertical external surfaces (walls). Product has excellent performance because it acts as a primer, correction and finishing.

SEGMENTS OF USE AND APPLICATIONS

- Plaster and concrete
- Exposed walls
- Fiber Cement
- About ink PVA and Acrylic
- About texture.

PREPARATION OF THE SURFACE

For a good grip and satisfactory results surfaces should be clean, regulated, rough, dry and free from sand, dust, grease, oil or release agents. Treat cracks and fissures with REISCRYL® acrylic sealant siliconized.

HOW TO USE

Should be applied 2 to 3 coats in case of new paint recommend that the first coat should be applied as a primer diluted **IMPERMEABILIZANTE PAREDE** up to 10% water. Interval 6 hours between coats.

APPLICATION: Can be applied by brushes or roller.

CAUTION: DO NOT APPLY THE PRODUCT IN RAINY DAYS.

Clean tools using water.

APPROXIMATE YIELD: 300 to 400 g/m²/coat.

NOTE: Greater consumption always in the first coat, reduction in the second and third coat. These figures may vary with the texture and temperature.

BENEFITS

- Easy handling and application of cold;
- Continuous application without amendments;
- Non-toxic;
- After application, does not transmit smells;
- **Does not emit volatile gases (VOC).**

CHARACTERISTICS AND PERFORMANCE

| PROPERTIES | IMPERMEABILIZANTE PAREDE |
|--------------------------|---|
| Appearance | Liquid thick white, flexible and elastic. |
| Resistance | Resistant to acid rain and water. |
| Ph 77°F (25°C) | 8 to 9.5 |
| Total drying, maximum | 24 to 48 hours |
| Solvent exemption | Positive |
| Stability aging sunlight | Ultraviolet resistant |
| Density | 1.35 a 1.50 g/cm ³ |
| Packaging | - Bucket 3,6 Kg - Bucket 18 Kg - Drum de 200 kg |

HEALTH AND SAFETY

Use protective glasses and rubber gloves. Direct contact with the skin should be avoided. In case of contact with the skin or eyes, wash immediately with abundant water and consult a doctor and inform the type of product.

STORAGE

IMPERMEABILIZANTE PAREDE should be stored in a dry, covered and ventilated location at around 77°F (25°C).

VALIDITY AND STORAGE

9 months from date of manufacture in a dry and ventilated place in its original package.