

Liquid Stucco

STUCRET® 303

STUCRET® 303 is a bonding adhesive for plastering cement floors, formulated with synthetic resins, latex and additives. Its purpose is to correct and fill small cavities during the polishing of the floor surface.

APPLICATION

STUCRET 303 is applied to the floor when sanding is done between 100 or 120 metallic sandpaper, involving the sanding dust with the product, forming a mud and at the same time filling the pores and cavities by means of agglutination.

Before starting the application with **STUCRET® 303**, the surface must be moistened to help absorption. It can be applied by pouring or using a backpack pump spraying on the floor surface.

Spread **STUCRET® 303** + process dust using a soft broom or squeegee until a mud forms and then use the sander to force the mud to fill the cavities.

To correct cavities above 5mm, it is recommended to use **STUCRET® 303** with **REPAROX® PI** mortar. If you choose to use **STUCRET® 303** + **REPAROX® PI**, the surface must be washed well to completely remove dust.

Apply **STUCRET®** + **REPAROX® PI** already softened, using a trowel or squeegee over the entire surface. After plastering, you must wait 24 to 72 hours to remove the plaster with appropriate equipment using 50 to 100 grit sandpaper.

The process described is a guide for professionals and can be adapted as long as the same result is obtained.

USE SEGMENT

- Plastering of cement floors;
- Concrete, granite, korodur and others;
- Recovery and repairs in general.

BENEFITS

- * Ease of use during the process;
- * Excellent adhesion between materials;
- * Plugging 4 to 5mm of the cavities;
- * Hardening without shrinkage.

APPLICATION LIMITATIONS

It should not be applied in environments below 50°F or above 95°F.

CHARACTERISTICS AND PERFORMANCE

Chemical composition	Latex Aqueous Dispersion
Appearance	Milky white liquid
Density	1,02 g/cm ³
pH	7 to 8
Performance	250 a 300g/m ²
Packaging	20L - 50L drum and 200 L drum

HYGIENE AND SAFETY

Users must wear protective glasses and rubber gloves. Direct contact with the skin should be avoided (may cause irritation). In case of contact with skin or eyes, wash immediately with plenty of water and consult a doctor. Keep out of reach of children and animals.

STORAGE

Store in a dry and ventilated place at a temperature below 30°C (86°F), in the original sealed packaging.

VALIDITY: 12 months from the date of manufacture.

Reis e Reis Indústria e Comércio Ltda
Rua Wilton Reis Costa, 220
Eldorado Centro Industrial e Empresarial
São José dos Campos / SP CEP 12238-574
Phone/Fax: +55 12 3966 9977
e-mail: vendas@reisereis.com.br
www.reisereis.com.br

Our technical advice concerning the application of the product is made verbally, in writing and through demonstration depending on the interest of the customer.

It should be noted that the application of the product is a precision process and when it is not applied by Reis e Reis, the company disclaims any responsibility; therefore, the responsibility is that of the customer. Regarding the storage and use of the product, any resulting change in its properties will be the complete responsibility of the customer.

The liability of Reis e Reis will be limited to any damage or loss in value of the goods supplied by the company and used by the customer. We guarantee the unquestionable quality of our products in accordance with our terms of sale and supply.