

## Stucco for Superficial Treatment

# RR3000

### PRODUCT

RR 3000 is an adhesive designed for stucco floors, formulated for synthetic resins, latex and special additives. It has the purpose of correcting and filling small cavities during polishing of the surface of the floor.

### APPLICATION

It is applied on the floor at the time that the sanding is done, mixing the dust with the product, forming a paste while plugging the pores by means of agglutination.

To fix cavities larger than 5 mm, it is recommended that you use **RR 3000** with mortar **Reparox**.

If you choose to use **RR 3000 + Reparox**, the surface should be thoroughly washed to remove all dust.

Apply **RR 3000 + Reparox** already spread using a steel trowel or squeegee.

After stucco **RR 3000 + Reparox** it is necessary to wait 12 hours before removing the plaster with proper equipment.

### SEGMENTS OF USE

Stucco concrete floors Concrete floors, quartz Composite floors, Korodur and others Recovery and general repairs

### BENEFITS

Provides hardening without retraction;  
Provides excellent adhesion to the substrate.

### CHARACTERISTICS AND PROPERTIES

| CHARACTERISTICS | RESULTS                          |
|-----------------|----------------------------------|
| Chemical base   | Aqueous dispersion of copolymers |
| Appearance      | Milky white liquid               |
| Boiling point   | 212 F                            |
| Density         | 1.02                             |
| pH 77F (25C)    | 7 to 8                           |
| Yield           | 250g/m <sup>2</sup>              |

### CLEANLINESS AND SAFETY

Users should use protective glasses and rubber gloves. Direct contact with the skin should be avoided (can cause irritation). In case of contact with skin or eyes, wash immediately and abundantly with water, consult a doctor and inform the type of product.

Keep packages out of the reach of children, animals and sources of heat.

### STORAGE

**RR 3000** should be stored in a dry and ventilated place in unopened package.

### VALIDITY

9 months in sealed package.