

Mold Release Emulsion-based Mineral

RR DESMOLDE® CD

PRODUCT

RR Desmolde® CD is an emulsion formulated with mineral additives for use as a high performance release agent for wood or metal shapes. The goal is to prevent adherence of concrete and increase useful life and shapes.

RR Desmolde® CD is recommended for visible concrete as it allows it to obtain smoother surfaces, perfect edges and prevents sticking of the concrete to the concrete forms.

APPLICATION

RR Desmolde® CD may be applied by brush, roller or spraythrough a nozzle. Must saturate all forms of the surface without presenting puddles or excess.

It is recommended for each application, shake the container with the product.

The product can be applied pure or mixed in water, at a maximum dilution of 1:10.

After application, wait 30 minutes to lay the concrete.

RENDIMENTO

Pure product: wood and metal molds 50 m²

Resin wood form	Plasticized form	Metallic form
Dilution 1:5 60m ² /L	Dilution 1:5 200m ² /L	Dilution 1:5 200m ² /L
Dilution 1:10 100m ² /L	Dilution 1:10 400m ² /L	

BENEFITS

- Easy handling;
- Perfect disassembly;
- Increases flexibility in work;
- Greater reuse of forms;
- Great appearance;
- Does not stain the surface of the concrete;
- Increases the lifetime of the forms.

CHARACTERISTICS AND PERFORMANCE

PROPERTIES	RR Desmolde®CD
Aspect	White- colored liquid
Solubility	Emulsifiable in water
Viscosity	< 162cps = 0,06 gr/cm ³
Relative specific mass 77F(25C)	0,87
pH 25°C	7 - 8
Absence of solvent	Positive
Package	Bucket 3.6L - 18L - Drum 180 L

INDIVIDUAL PROTECTION EQUIPMENT

Use glasses and PVC gloves.

HEALTH AND SAFETY

Keep container closed out of the reach of children, pets and heat sources. Keep the environment ventilated during application and drying. In case of contact with skin or eyes, wash the affected area with plenty of water; if swallowed, do not induce vomiting, seek medical advice immediately and inform the type of product.

STORAGE

RR Desmolde® CD should be stored in a dry and ventilated place at 25°C (77°F).

VALIDITY

24 months

Reis e Reis Indústria e Comércio Ltda

Rua Wilton Reis Costa, 220

Eldorado Centro Industrial e Empresarial

São José dos Campos / SP CEP 12238-574

Phone/Fax: +55 12 3966 9977

e-mail: vendas@reisereis.com.br

www.reisereis.com.br

Our technical advice concerning the application of the product is made verbally, in writing and through demonstration depending on the interest of the customer.

It should be noted that the application of the product is a precision process and when it is not applied by Reis e Reis, the company disclaims any responsibility; therefore, the responsibility is that of the customer. Regarding the storage and use of the product, any resulting change in its properties will be the complete responsibility of the customer.

The liability of Reis e Reis will be limited to any damage or loss in value of the goods supplied by the company and used by the customer. We guarantee the unquestionable quality of our products in accordance with our terms of sale and supply.