

Demoulding for Wood and Metallic Forms

RR DESMOLDE® STANDARD

PRODUCT

RR Desmolde® Standard is a water-soluble oil containing no solvents, salts or acids. It does not cause any chemical effect on the concrete and forms.

RR Desmolde® Standard forms protect against rust and metallic forms of wood against dryness, increasing the useful life of the forms which can be used a greater number of times.

RR Desmolde® Standard is recommended for visible concrete as it allows it to obtain smoother surfaces, perfect edges and prevents sticking of the concrete to the concrete forms.

APPLICATION

RR Desmolde® Standard is applied to forms of any type: wood, plastic, plywood, metallic, etc...providing an excellent and stainfree finish, and the best economy by high rates of reuse of forms.

RR Desmolde® Standard is soluble in water and can be applied pure or mixed 1:1 to 1:5.

To dilute it put RR Desmolde® Standard in a container and add up to 5% of water, mix well, then put the rest of the water in the proportion above, always mixing evenly.

The application can be made with brush, roller, low pressure spray, or by immersion. It is recommended that before each application shake the packaging of the pure product.

YIELD

| Resin wood form | Plasticized form | Metallic form |
|----------------------|--------------------------|--------------------------|
| Diluition 1:5 60m²/L | Diluition 1:5 200m²/L | Diluition 1:5 200m²/L |

After application wait 1 hour before laying concrete.

BENEFITS

- Easy handling;
- Perfect disassembly;
- Increases flexibility in work
- Ecological product;
- Great appearance;
- After application does not give odor;
- Increases the lifetime of the forms.

CHARACTERISTICS AND PERFORMANCE

| PROPERTIES | RR Desmolde® Standard |
|--------------------------------------|--------------------------------|
| Aspect | White - colored liquid |
| Solubility | Emulsifiable in water |
| Viscosity | < 65 cps = 0.02 g/cm³ |
| Relative specific mass 77°F(25°C) | 0,87 |
| pH 25°C | 7 - 8 |
| Absence of solvent | Positive |
| Package | Bucket 3.6L - 18L - Drum 180 L |

INDIVIDUAL PROTECTION EQUIPMENT

Use glasses and PVC gloves.

HEALTH AND SAFETY

Keep container closed out of the reach of children, pets and heat sources. Keep the environment ventilated during application and drying. In case of contact with skin or eyes, wash the affected area with plenty of water; if swallowed, do not induce vomiting, seek medical advice immediately and inform the type of product.

STORAGE

RR Desmolde® CD should be stored in a dry and ventilated place at 25C (77F).

VALIDITY

24 months