

Waterproofing oil for coating treatment

BLOCK BS – Waterproofing oil

PRODUCT

RR OLEOFUGANTE is a waterproof oil for coating treatment with high potentiality of bead effect. Is indicated for protecting and preserving the surfaces against oil stains, grease and water absorptions. Shall be used as final finishing; it doesn't form any liquid membrane, yet it has a long durability inhibiting formation of stains on treated surfaces.

SEGMENTS OF USE

- Concrete Floors;
- Laminated Floors;
- Chip Floors;
- Natural Porous Floors;
- Porcelain Tiles;
- Facades.

BENEFITS

- Easy application
- Avoid penetration of dampness and salts
- Do not form scales or membranes
- Application may be internal and external
- Better appearance
- Better Durability
- Do not alter appearance
- High performance

PREPARATION OF SURFACE

The surfaces must be exempt of grease, oil, dust and humidity

APPLICATION

It's recommended to apply from 2 to 3 hands to lengthen durability. Between hands, one hour of intervals should be observed. It can be applied with foam roller, brusher or painting machine type *Airless system*.

NOTE: during application, care shall be taken against its flammability, avoiding proximity with any sources of flames or environments too hot.

YIELDING

Floor class 01: from 25m² to 30m² per liter. (Lapidated Concrete Floor, Porcelain, Marble, Granite...)

Floor class 02: from 8m² to 14m² per liter. (Polished Concrete Floor, Slate, Natural Ceramic Textured Marble, Basalt).

Concrete facades:

Roller application: 150 mL/m².

* The product consumption is reduced by up to **40%** when applied in paint type *Airless system*.



OBS .: Depending on the porosity of the floor and forms applications, the yield of the product per m² can vary.

PACKING: Plastic Tanks 5-20 - 50 liters drum of 200 liters.

CLEANLINESS AND SAFETY

The users shall use safety glasses, rubber gloves. Direct skin contact shall be avoided. In case of contact with skin or eyes, wash immediately with abundant water, consult a physician and inform the type of the product. Keep the packing out of children reach, animals and heat sources.

STORAGE

The product should be stored in a dry, covered and ventilated at 25°C. (77°F).

EXPIRATION

9 months into original sealed packing.

