

Protective Mask

RR CONFILME®

PRODUCT

RR CONFILME® is a liquid protective mask responsible for protecting surfaces from paint overspray and primers during the painting process.

It forms a protective non-adherent film, easily removable with water.

APPLICATION

RR CONFILME® is applied with the aid of an air gun regulated between 45 to 50 **psi** and spread with a sponge or lint-free cloth.

RR CONFILME® can be applied over any automotive paint and also plastic, friezes, glass, vinyl and the motor compartment.

RR CONFILME® forms a protective layer and must cover the entire surface to be protected. Apply one or two coats. If the surface is waxed, two layers should be applied or until there is complete adherence of **RR CONFILME®** over the area to be protected.

It is recommended that it be applied by qualified professionals.

DRYING :77 F (25C) - 30 to 40 minutes
30 a 40 minutes

CATALYSIS OR DILUTION

Not necessary.
Product is ready for use.

SEGMENTS OF USE

- Automotive
- Marine
- Aerospace

BENEFITS

- Protects surfaces against contaminants;
- Time saving;
- Easy to clean;
- Eliminates wrapping phase;
- Easy and fast application;

CHARACTERISTICS AND PROPERTIES

CHARACTERÍSTICS	RESULTS
Chemical Base	Dispersal in water, alcohols and additives
Appearance	Semi-transparent white liquid
Boiling point	212 F / 100°C
Density	1,02
pH 25° C, 77F	7 to 8
Yield	1 liter: 2 medium-sized cars



CLEANLINESS AND SAFETY

Users should use safety glasses, safety mask and rubber gloves. Contact with the skin should be avoided (can cause irritation). In case of contact with skin or eyes, wash immediately and abundantly with water and consult a doctor.

Keep out of reach of children and animals.

Packaging: 5L -10L drums.

Cleanup: Wash the tools with water or alcohol.

STORAGE

RR CONFILME® must be stored in a dry, ventilated place and far from sources of ignition.

Expiration: 9 months in unopened package.