

## Sealer Water Based

# RR SELADOR®

### PRODUCT

RR SELADOR® is used for sealing pores having excellent flatness and finish, providing a suitable base for the application of wax **RR Wax**.

It can be used on high floors or low porosity, ex: vinyl flooring, concrete, marble, slate and granilite.

### FLOOR PREPARATION

The surface must be perfectly clean, free of dust, sand, waxes, resins, grease or any dirt.

### APPLICATION

Apply RR SELADOR pure in 02 layers with the aid of a MOP or soft cloth. Drying should wait interval between the layers 15 to 30 minutes.

### YIELD

It varies according to type of floor:

- Vinyl flooring and marble: 60 to 80m<sup>2</sup>
- Concrete, granilite and slate: 50 to 60m<sup>2</sup>

### BENEFITS

- Easy handling and application;
- Excellent abrasion resistance;
- Prevents waste;
- Excellent adhesion to the surface;
- Prevents risks;
- Quick release;

### HEALTH AND SAFETY

Users should wear protective goggles and rubber gloves. Direct contact with the skin should be avoided (may cause irritation). In case of contact with skin or eyes, rinse immediately with plenty of water and consult a doctor. Keep out of reach of children, animals and heat sources.

### CHARACTERISTICS AND PERFORMANCE

PROPERTIES	RR SELADOR®
Composition	Aqueous polymer and additives
Appearance	Milky Liquid
Color	White
Odor	Characteristic
pH	7,0 - 8,0
Specific weight	1,02 - 1,03 g/cm <sup>3</sup>
Content of active	17,0 - 18,5%
Yield	50 à 60m <sup>2</sup> per liter
Package	Gallon 3,78L and bucket 18L

### STORAGE

RR SELADOR® should be stored in dry and ventilated at 25°C.

### VALIDITY

12 months