

## SHINY WET METALLIC WAX ACRYLIC

# RR WAX®

### PRODUCT

**RR WAX®** is an acrylic wax for used- or new floors. It has indispensable characteristics of superior shine, resistance to traffic, scratches, marks and dirt due to molecules of high weight, polymers and union of molecules of high density producing a plastic barrier. Its exclusive durability provides intense shine with mirror-like appearance with greater duration between maintenance cycles. It is totally transparent, non-slip and non-yellow. It is also excellent for maintenance of big areas with intense traffic.

Due to its excellent quality, this wax provides an unequalled cost/benefit, giving economy of work in numerous applications.

### PREPARATION OF THE FLOOR

The floor should be completely washed to remove other sealers and old wax with a machine of 175 RPM with a Scotch-Brite disk.

### APPLICATION

The floor has to be perfectly dry and clean before beginning the application. For a better resistance and appearance apply two layers of **RR SELADOR®**. Apply the wax in thin layers using a mop, foam or soft cloth.

We recommend applying from 3 to 5 layers depending on the type of floor and traffic.

Apply a layer without walking on the same area until it is 100% dry. Let dry from 15 to 30 minutes. Polishing between layers is not necessary; the floor will attain an intense shine and be non-slippery conforming to ASTM 2047.

### DAILY MAINTENANCE

Use a mop once a day or more if necessary, until the floor keeps free of powder and dirt. The maintenance can be done with a damp cloth, water and neutral soap.

### BENEFITS

- Easy handling and application
- Excellent resistance to abrasion
- Excellent adherence to the surface
- Quick drying

### UTILIZATION

- Vinyl flooring
- Concrete
- Slate
- Granite
- Wood floors
- Floors with epoxy tint

### CHARACTERISTICS AND YIELD

PROPERTIES	RR WAX
Appearance	Smooth liquid
Color	White
Fragrance	Characteristic of wax
pH	8.0 – 9.0
Specific weight	1.024 – 1.035 g/cm <sup>3</sup>
Percentage of active ingredients	22.0 – 25.0 %
Yield	50 to 60 m <sup>2</sup> per liter
Package	1 L, 3.6 L, 5 L, 18 L, 50 L, 180 L
Composition	Acrylic polymers, resins, additives

### CLEANLINESS AND SAFETY

Users should use safety glasses and rubber gloves. Direct contact with the skin should be avoided (can cause irritation). In case of contact with the skin or eyes, wash immediately with abundant water and consult a doctor. Keep out of the reach of children and animals and sources of heat.

### STORAGE

**RR WAX®** should be stored in a dry location and ventilated at 77 F (25 C)

**Expiration:** 12 months

*Our technical advice concerning the application of the product is made verbally, in writing and through demonstration depending on the interest of the customer.*

*It should be noted that the application of the product is a precision process and when it is not applied by Reis e Reis, the company disclaims any responsibility; therefore, the responsibility is that of the customer. Regarding the storage and use of the product, any resulting change in its properties will be the complete responsibility of the customer.*

*The liability of Reis e Reis will be limited to any damage or loss in value of the goods supplied by the company and used by the customer. We guarantee the unquestionable quality of our products in accordance with our terms of sale and supply.*

Rua Wilton Reis Costa, 220 - Cond.Ind. Eldorado  
São José dos Campos / SP CEP 12238-574

Fone/Fax: (12) 3966-9977

e-mail: [vendas@reisereis.com.br](mailto:vendas@reisereis.com.br)

Home-page: [www.reisereis.com.br](http://www.reisereis.com.br)

REV: 280307